

HP rp3000 Point of Sale Overview



© 2004 Hewlett-Packard Development Company, L.P.
The information contained herein is subject to change without notice.



Contents

- HP strategic overviews and positioning
- Product information
 - Portfolio
 - HP rp3000 point of sale solution
 - Peripherals
- Solution value proposition

HP Point of Sale Portfolio

HP rp3000 point of sale solution

Optimized for mid-market and smb retailers



Windows® Vista® Business with
downgrade to Windows XP
Professional

FreeDOS

HP rp5700 point of sale solution

Flexible and stable POS, built to last



Windows® Vista® Business with
downgrade to Windows XP
Professional

Microsoft Windows Embedded
for Point of Service (WEPOS)
FreeDOS

Highlights:

- Efficient: Space-saving footprint and integration tray maximize counter, color-coded I/O ports aid in easy setup
- Retail-ready: low-power Intel® Atom™ processor is protected by a steel chassis and tested to 40° C
- Secure: locking cover hides ODD and power button
- Attractive: HP branding, clean back panel and integration tray present a sleek, pulled together look for customers

Highlights:

- Reliable: rugged design backed by a 3-year warranty
- Flexible: open standards and additional connectivity
- Green: Energy Star compliant power supplies, EPEAT gold
- Secure: optional RAID, removable hard drive
- Powerful: choice of high-performance Intel processors
- Stable: 5-year lifecycle

HP POS Accessories

Cash Drawer



MSR w/monitor
bracket



POS Keyboards with
and w/o MSR

Barcode Scanner



Thermal Receipt
Printer



15" Touchscreen
Monitor



Hybrid Receipt
Printer with and
w/o imaging



New!



Customer Pole
Display

Optimized for mid-market and smb retailers HP rp3000 point of sale solution



| Features | Customer Benefits |
|--------------------------|---|
| Retail Hardened Design | Designed from the ground up to withstand the rigors of retail environments |
| Powered USB (12V / 24V) | Connect and power POS peripherals from the rp3000 system |
| Powered Serial | 2 RS232 Serial Ports (configurable to 5V and 12V) allowing connection to legacy peripherals |
| Expandability | Full-height PCI slot (or optional PCIe x1) enables installation of multi-monitor, additional ports, etc |
| Intel Atom processor | Low-heat processor helps ensure system keeps cool, provides processing power needed for retail |
| Retail peripherals | Solution optimized and tested with full portfolio of HP branded peripherals |
| HP Integration Tray | Consolidate system and peripherals and neatly organize cables for clean appearance |
| Security | Lockable drive bays restrict tampering and support for Kensington, Noble and padlocks |
| 3 year standard warranty | <ul style="list-style-type: none">•HP award winning warranty•Parts available for up to 8 years after launch•HP Care Pack services available for |



HP point of sale solution rp3000 point of sale specifications



SPECIFICATIONS

PROCESSOR: Intel® Atom™ 230

OPERATING SYSTEM: Windows® Vista® Business with downgrade to Windows XP Professional
FreeDOS

SYSTEM MEMORY: Dual Channel, PC2-3200, PC2-4200, or PC2-5300, PC2-6400 DDR2

HARD DRIVE: SMART III serial ATA 3.0Gb/s

NIC: Broadcom 5764M

Connectivity: 6 USB 2.0; plus 2 additional USB+POWER (1 @ 12V, 1 @ 24V)
2 serial individually configurable to power 5V & 12 V

GRAPHICS: Intel GMA 950

CHIPSET: Intel 945GC

WARRANTY: 3 year on-site

HP rp3000 POS Solution

A closer look at the basic point of sale “stack”



Note: other hp branded peripherals available to customize the solution stack

HP rp3000 POS System: Connectivity



| | |
|---|--|
| 150W internal supply, to support system and powered retail peripherals | 2 standard powered USB ports (12V and 24V) |
| Active PFC, auto-sensing voltage power supply | 2 power cable RS232 ports |
| Full height PCI slot standard, with optional PCIx1 card support (can only support one or the other), can support dual head graphics | 6 standard USB 2.0 ports |
| Color coded i/o ports for ease of set up | 10/100/1000 NIC |
| Standard audio line in and out ports | 2 standard PS/2 ports |
| VGA port for integrated graphics | Support for Kensington, Noble, and pad locks |

HP rp3000 vs. rp5700 point of sale: System Comparison



| | rp3000 | rp5700 |
|--|--|---|
| Target Market | Small to mid-sized businesses in need of basic POS | Mid-sized to Large businesses needing flexibility and stability |
| Retail-hardened design | Yes | Yes |
| Standard Powered USB and Serial ports | Yes | Yes |
| Tested to a 40°C environment | Yes | Yes |
| HP BIOS | Yes | Yes |
| Environmentally-friendly | Yes | Yes |
| Expandability | 1 PCI (Optional PCIe x1) | 2 PCI, PCIe x1 |
| RAID capability | No | Yes |
| Front USB | No | Yes |
| Global Skus Available | No | Yes |
| Lifecycle | 3 years | 5 years |
| Tool-less Chassis | No | Yes |

HP rp3000 POS versus HP rp5700 POS



| | rp3000 | rp5700 |
|--------------------------------------|-----------|----------------|
| Operating Systems¹ | | |
| Vista Downgraded to XP Pro | ✓ | ✓ |
| Windows Vista Business 32 | Note 5 | ✓ |
| Microsoft POS Ready (WEPOS) | 2Q09 | ✓ |
| FreeDOS | ✓ | ✓ |
| Linux RedHat Certified | N/A | ✓ |
| Linux SuSe Novell Certified | N/A | ✓ |
| Chipset | | |
| Intel Q963 Express | | ✓ |
| Intel 945 GC/ICH7 | ✓ | |
| Processors | | |
| Core 2 Duo E6400e (2.13 GHz) | | ✓ |
| Pentium Dual Core E2160 (1.8 GHz) | | ✓ |
| Celeron CEL440 (2.0 GHz) | | ✓ |
| Intel Atom N230 (1.6GHz) | ✓ | |
| Memory | | |
| DIMM Slots | 2 | 4 |
| DDR2 Memory Size (Min - Max) | 1 to 2 GB | 512 MB to 4 GB |
| Hard Drives | | |
| 80 and 500 GB | N/A | ✓ |
| 160 and 250 GB | ✓ | ✓ |
| Removable Drive (ODD Slot) | N/A | ✓ |
| Optical Drives | | |
| 16x / 48x DVD-ROM | ✓ | ✓ |
| DVD+/-RW Lightscribe | ✓ | ✓ |
| NIC / Communications | | |
| Integrated Broadcom NetXtreme (GigE) | | ✓ |
| Integrated Broadcom 5764 (GigE) | ✓ | |

N/A = Not Available; AMO = After Market Kit

¹ For rp3000, initial OS support is Vista Downgrade to XP Pro; Vista and WEPOS to be added later

² On the rp5700 POS, one of the PCI Full-Height Slots is reserved for the Powered USB+ Port Card

³ PCIe x1 Riser Card is available as an AMO Kit and can be inserted in the PCI Full-Height Slot

⁴ ADD2 Slot not available on rp3000; however, PCIe x1 Graphics Card can be used for dual display

⁵ Windows Vista Business 32 available from Recovery CD on the Vista Downgraded to XP Pro CD

| | rp3000 | rp5700 |
|---|--------------------------|------------------------|
| I/O Ports / Connectivity | | |
| RJ45 (GigE) | 1 | 1 |
| PS/2 Ports (e.g., Keyboard, Mouse) | 2 | 2 |
| USB Ports (2.0 Volts/Standard USB) | 6 | 6 (4 Rear, 2 Front) |
| USB+ Powered Ports (V = Volts) | each +24V; 1 each +12V | each +24V; 3 each +12V |
| Total USB Ports | 8 | 10 (8 Rear, 2 Front) |
| RS232 Serial/COM Ports* | 2 | 2 |
| *Power Configurable (V = Volts) | +5V or +12V | +5V, +9V or +12V |
| Audio Line-Out & Audio Line-In | 1 each | 1 each |
| Parallel Port | N/A | ✓ |
| VGA Port | 1 | 1 |
| Expansion Slots | | |
| PCI Full-Height Slots | 1 | 2 (see note 2) |
| PCIe x1 Slot | see note 3 | 1 |
| ADD2/SDVO Slot (Dual Display) | see note 4 | 1 |
| Total Expansion Slots | 1 | 4 (see note 2) |
| Security | | |
| Lockable Front Cover | ✓ | N/A |
| Wall-Mount / Security Sleeve (AMO Kit) | N/A | ✓ |
| Power Supply | | |
| Internal, 240 Watt, Auto Switching, 80+ | | ✓ |
| Internal, 150 Watt, Auto Switching | ✓ | |
| Miscellaneous / Mechanical | | |
| Dimensions | 5.16"W x 8.27"D x 3.27"H | 13.4"W x 15"D x 3.94"D |
| RAID (Installed from HP Factory) | N/A | ✓ |
| 40° C (104° F) Ambient Thermal Support | ✓ | ✓ |
| Servicability | Non-Toolless | Toolless |
| EPEAT Compliant (Environmental) | N/A | ✓ |
| Product Lifecycle | 3 years | 5 years |
| Warranty (Parts/Labor/Service) | 3/3/3 years | 3/3/3 years |



HP POS Peripherals & Accessories

Current



Cash Drawer



POS Keyboard



Magnetic Strip Reader (MSR)



Thermal Receipt Printer



Barcode Scanner



15" Touchscreen Monitor

New (available October'08)



rp3000
Integration Tray
(available 12/15)



POS Keyboard
w/MSR



MSR with
mounting bracket



Hybrid Receipt
Printer



Hybrid Receipt
Printer
w/Imaging



Customer Pole
Display

HP point of sale solution

Thermal Receipt Printer specifications



SPECIFICATIONS

| | |
|------------------------|--|
| Type | Single-station two color and monochrome thermal printer |
| Speed | Prints up to 74 lines per second |
| ReceiptWare | Flexible receipt editing software for customizing your sales receipts |
| Spill-resistant | Built-in liquid dam with drainage prevents damage to printing mechanism |
| Memory | 4 MB Flash Memory for custom tasks |
| Paper | 90mm paper roll capacity; quickly and easily replaced w/Clamshell™ drop-in paper loading |
| Interface | 24V powered USB |
| Dimensions | 5.34 x 5.66 x 7.24 in (H x W x D) (134 x 144 x 184 mm) |
| Warranty | 1 year limited (parts replacement) 3 year onsite with purchase of rp3000 or rp5700 platform |

HP point of sale solution

Hybrid Printer specifications



SPECIFICATIONS

| | |
|-------------------|--|
| Hybrid | Two-color or monochrome thermal printer on top for receipts; Impact slip printer on the bottom for inserted forms and checks |
| MICR | Built in Magnetic Ink Character Recognition for check reading and validating |
| Scanner | Scans both sides of check or ID in a single feed |
| Speed | Prints up to 56 lines per second |
| Memory | 2MB; shared for graphics, logos, user defined characters and user data storage |
| Paper | 90mm paper roll capacity; quickly and easily replaced w/Clamshell™ drop-in paper loading |
| Interface | 24V powered USB |
| Dimensions | 6.5 in. x 11.4 in. x 6.6 in. (W x D x H) (165.10 mm x 289.56 mm x 167.64 mm) |
| Warranty | 1 year limited (parts replacement) 3 year onsite with purchase of rp3000 or rp5700 platform |

HP point of sale solution

Hybrid Printer w/Imaging specifications



SPECIFICATIONS

Hybrid Two-color or monochrome thermal printer on top for receipts; Impact slip printer on the bottom for inserted forms and checks

Imaging Create image files for Check 21 processing

MICR Built in Magnetic Ink Character Recognition for check reading and validating

Scanner Scans both sides of check or ID in a single feed

Speed Prints up to 56 lines per second

Memory 2MB; shared for graphics, logos, user defined characters and user data storage

Paper 90mm paper roll capacity; quickly and easily replaced w/Clamshell™ drop-in paper loading

Interface 24V powered USB

Dimensions 6.5 in. X 13.25 in. X 6.65 in. (W x D x H)
(165.10 mm X 336.55 mm X 168.91 mm)

Warranty 1 year limited (parts replacement)
3 year onsite with purchase of rp3000 or rp5700 platform



HP point of sale solution

Integrated Keyboard and MSR specifications



SPECIFICATIONS

Swipe Bi-directional swipe reads 1, 2 or 3 tracks of magnetic information

Keys 106-position key layout, with 28 configurable keys

Touchpad Integrated, with two mouse buttons

Spill-resistant IP54 spill and dust resistant key area

Design Attachable keyboard feet to elevate the rear of the keyboard

Interface USB

Dimensions 14.2 x 7.8 x 1.5 in (H x L x W)
(36.0 x 19.8 x 3.8 cm)
Optimum space efficiency for retail environment

Warranty 1 year limited (parts replacement)
3 year onsite with purchase of rp3000 or rp5700 platform

HP point of sale solution

Customer Display Pole specifications



SPECIFICATIONS

| | |
|----------------------|--|
| Display Type | Vacuum Fluorescent Display, Blue Green |
| Text | 5 x 7 dot matrix, cursor; 20 columns, 2 lines |
| Command Modes | Supports multiple command modes with EPSON set as default |
| Base | Standard rectangular base or optional circular mini-base for stability in a small space |
| Interface | USB |
| Dimensions | Panel: 225 x 50 x 86mm Pole: 3 supports included: 130mm each |
| Warranty | 1 year limited (parts replacement) 3 year onsite with purchase of rp3000 or rp5700 platform |

HP point of sale solution

Mag Stripe Reader specifications



SPECIFICATIONS

| | |
|--------------------------|--|
| Flexible | Free-standing unit, mounted to a surface, or attached to an HP touch screen or flat panel |
| Direction | Bi-directional |
| Tracks | Reads up to three tracks of magnetic information in a single swipe |
| Indicators | Tri-colored LED, beeper |
| Interface | USB |
| Dimensions | 3.5 x 1.3 x 1.1 in (L x W x H) (9 x 3.4 x 2.8 cm) |
| Mounting Brackets | Included for mounting to HP Touchscreen or displays with standard VESA bracket |
| Warranty | 1 year limited (parts replacement) 3 year onsite with purchase of rp3000 or rp5700 platform |

HP point of sale solution

Cash Drawer specifications



SPECIFICATIONS

| | |
|-------------------|--|
| Quality | Heavy duty, robust construction ensures durability and long life |
| Interface | Operates through HP USB Receipt Printer |
| Till | Adjustable dividers separate and organize sections for bills and coins |
| Lock | Four-function offering levels of security: locked closed, locked open, online and manual open. |
| Dimensions | 4.9 x 16 x 16.7 in (H x W x D) (12.5 x 40.6 x 42.4 cm) |
| Warranty | 1 year limited (parts replacement) 3 year onsite with purchase of rp3000 or rp5700 platform |

HP point of sale solution

Touchscreen specifications



SPECIFICATIONS

| | |
|-----------------------------|---|
| Type | 15-inch Active Matrix TFT |
| Design | Rugged, stable tilt base, and buttons located on side all "designed for touch" |
| Touch | Surface Acoustic Wave (SAW) touch technology for accurate input |
| Glass | Chemical-resistant glass offers a more durable alternative to film-coated display screens |
| Flexibility | Functions as countertop or wall-mountable; VESA mount optional |
| Viewing Angle | 120 degrees horizontal/100 degrees vertical |
| Dimensions (w/stand) | 12.2 x 13.8 x 6.9 in. (H x W x D) (31.0 x 35.0 x 17.5 cm) |
| Warranty | 3 year limited (parts replacement) |

HP point of sale solution

Scanner specifications



SPECIFICATIONS

Design Durable, light-weight hand-held scanner with hands-free Intellistand™

Type Bi-directional

Speed 100 scans per second

Working Range 17 inches (43cm) on UPC and EAN symbols

Interface USB

Weight 5.15 oz

Dimensions 6 H x 2.5 L x 3.3 W in (15.2 x 6.3 x 8.4 cm)

Warranty 1 year limited (parts replacement)
3 year onsite with purchase of rp3000 or rp5700 platform